

CEBORA CASTERS

CEBORA casters - Now available through Albion!

Introducing The Cebora S4 Series -

Light medium duty 304 stainless steel casters

Available in 3", 4", and 5" sizes, and rigid, swivel, and total lock models

Swivels come standard with 250°F rated grease seal



Part Number	Tread Width (in.)	Capacity (lbs.)	Overall Height (in.)	Top Plate (in.)	Bolt Hole Pattern (in.)	Swivel Radius	Wheel Type	Bearing
S4PB03051R	1.25	285	4 3/32	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Polyolefin	Delrin
S4PB03051S	1.25	285	4 3/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	2 .75	Polyolefin	Delrin
S4PB03051ST	1.25	285	4 3/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4.5	Polyolefin	Delrin
S4PB04051R	1.25	285	5 1/16	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Polyolefin	Delrin
S4PB04051S	1.25	285	5 1/16	3 3/4 x 2 2/3	1 3/4 x 2 7/8	3 1/3	Polyolefin	Delrin
S4PB04051ST	1.25	285	5 1/16	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4.5	Polyolefin	Delrin
S4PB05051R	1.25	285	6 5/32	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Polyolefin	Delrin
S4PB05051S	1.25	285	6 5/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4	Polyolefin	Delrin
S4PB05051ST	1.25	285	6 5/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4 7/8	Polyolefin	Delrin
S4TR04041R	1.25	285	5 1/16	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	High-Temp phenolic	Plain
S4TR04041S	1.25	285	5 1/16	3 3/4 x 2 2/3	1 3/4 x 2 7/8	3 1/3	High-Temp phenolic	Plain
S4TR04041ST	1.25	285	5 1/16	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4.5	High-Temp phenolic	Plain
S4TR05041R	1.25	285	6 5/32	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	High-Temp phenolic	Plain
S4TR05041S	1.25	285	6 5/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4	High-Temp phenolic	Plain
S4TR05041ST	1.25	285	6 5/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4 7/8	High-Temp phenolic	Plain
S4XA03051R	1.25	285	4 3/32	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Urethane on Polypropolene	Delrin
S4XA03051S	1.25	285	4 3/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	2 .75	Urethane on Polypropolene	Delrin
S4XA03051ST	1.25	285	4 3/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4.5	Urethane on Polypropolene	Delrin
S4XA04051R	1.25	285	5 1/16	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Urethane on Polypropolene	Delrin
S4XA04051S	1.25	285	5 1/16	3 3/4 x 2 2/3	1 3/4 x 2 7/8	3 1/3	Urethane on Polypropolene	Delrin
S4XA04051ST	1.25	285	5 1/16	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4.5	Urethane on Polypropolene	Delrin
S4XA05051R	1.25	285	6 5/32	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Urethane on Polypropolene	Delrin
S4XA05051S	1.25	285	6 5/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4	Urethane on Polypropolene	Delrin
S4XA05051ST	1.25	285	6 5/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4 7/8	Urethane on Polypropolene	Delrin
S4XR03028R	1.25	200	4 3/32	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Xtra soft round	Precision
S4XR03028S	1.25	200	4 3/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	2 .75	Xtra soft round	Precision
S4XR03028ST	1.25	200	4 3/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4.5	Xtra soft round	Precision
S4XR04028R	1.25	285	5 1/16	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Xtra soft round	Precision
S4XR04028S	1.25	285	5 1/16	3 3/4 x 2 2/3	1 3/4 x 2 7/8	3 1/3	Xtra soft round	Precision
S4XR04028ST	1.25	285	5 1/16	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4.5	Xtra soft round	Precision
S4XR05028R	1.25	285	6 5/32	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Xtra soft round	Precision
S4XR05028S	1.25	285	6 5/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4	Xtra soft round	Precision
S4XR05028ST	1.25	285	6 5/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4 7/8	xtra soft round	Precision
S4XS03051R	1.25	200	4 3/32	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Xtra-soft flat	Delrin
S4XS03051S	1.25	200	4 3/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	2 .75	Xtra-soft flat	Delrin
S4XS03051ST	1.25	200	4 3/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4.5	Xtra-soft flat	Delrin
S4XS04051R	1.25	285	5 1/16	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Xtra-soft flat	Delrin
S4XS04051S	1.25	285	5 1/16	3 3/4 x 2 2/3	1 3/4 x 2 7/8	3 1/3	Xtra-soft flat	Delrin
S4XS04051ST	1.25	285	5 1/16	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4.5	Xtra-soft flat	Delrin
S4XS05051R	1.25	285	6 5/32	3 15/16 x 2 23/32	1 3/4 x 2 7/8	N/A	Xtra-soft flat	Delrin
S4XS05051S	1.25	285	6 5/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4	Xtra-soft flat	Delrin
S4XS05051ST	1.25	285	6 5/32	3 3/4 x 2 2/3	1 3/4 x 2 7/8	4 7/8	Xtra-soft flat	Delrin

For rig only part numbers, replace two letter code with 'YA' (Example: S4YA05051S)