

# NX WHEELS

**Can your heavy duty nylatron wheel handle up to 7,200 lbs.?  
Ours can.**

Albion Trionix™ (NX) high impact polymer wheels are the definition of heavy duty wheels. These wheels are machined, instead of molded, giving them added strength. Our NX wheels deliver high performance, capacity, slide resistance and excellent rollability. Trionix™ features unique polymers that resist corrosion and most chemicals. These wheels feature a higher capacity than metal wheels, a temperature range of -15°F to 180°F, and hardness of 78-82 Shore D.

## TRIONIX™ WHEELS



Wheel Diam. (in.)	Tread Width (in.)	Capacity (lbs.)	Hub Length (in.)	Bearing ID (in.)	Part No.
4	2	2160	2-7/16	1/2	NX0422808
5	2	2160	2-7/16	1/2	NX0522808
6	2	2160	2-7/16	1/2	NX0622808
6	2-1/2	7200	3	3/4	NX0642812
6	3	7200	3-1/2	3/4	NX0652812
8	2	2160	2-7/16	1/2	NX0822808
8	2-1/2	7200	3	3/4	NX0842812
8	3	7200	3-1/2	3/4	NX0852812
10	2-1/2	7200	3	3/4	NX1042812
10	3	7200	3-1/2	3/4	NX1052812

Hub length and bearing ID are measured with top hats

## TRIONIX™ V-GROOVE WHEELS (NV)



**FEATURES:**

**Wheel Face:** V-Groove

**Finish:** Black

**Temperature Range:** -30°F to 220°F

Wheel Diam. (in.)	Tread Width (in.)	Capacity (lbs.)	Hub Length (in.)	Bearing ID (in.)	Groove Depth A (in.)	Groove Depth B (in.)	Part No.
4	2	2160	2-7/16	1/2	.88	.44	NV0422808
5	2	2160	2-7/16	1/2	.88	.44	NV0522808
6	2	2160	2-7/16	1/2	.88	.44	NV0622808
8	2	2160	2-7/16	1/2	.88	.44	NV0822808

Spanner is held in place with snap rings - no more lost top hats!

LET THE CASTER EXPERTS BE YOUR ONLY SOURCE FOR NYLATRON WHEELS - CALL (800) 835-8911 OR VISIT [WWW.ALBIONINC.COM](http://WWW.ALBIONINC.COM)

SEE REVERSE FOR MORE TRIONIX™ PRODUCTS